U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE ORM PTO-1390 (Modified) 781.403USWO TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR TO BE AS QUE 86 9 0 0 1 CONCERNING A FILING UNDER 35 U.S.C. 371 PRIORITY DATE CLAIMED INTERNATIONAL APPLICATION NO INTERNATIONAL FILING DATE 21 December 1998 PCT/F199/01063 21 December 1999 TITLE OF INVENTION CALL ROUTING APPLICANT(S) FOR DO/EO/US PALVIAINEN, Keijo Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information: This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include itens (5), (6), \boxtimes 3. (9) and (24) indicated below. The US has been elected by the expiration of 19 months from the priority date (Article 31). 4. A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) 5. is attached hereto (required only if not communicated by the International Bureau). has been communicated by the International Bureau. h 🖾 43 c.

is not required, as the application was filed in the United States Receiving Office (RO/US). m ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2))-6. a.

 is attached hereto. b.
 has been previously submitted under 35 U.S.C. 154(d)(4). Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) are attached hereto (required only if not communicated by the International Bureau). b.
 have been communicated by the International Bureau. c. \(\square\) have not been made; however, the time limit for making such amendments has NOT expired. 100 d. | have not been made and will not be made. M An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 8 9 An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)). An English language translation of the annexes of the International Preliminary Examination Report under PCT 10 Article 36 (35 U.S.C. 371 (c)(5)). A copy of the International Preliminary Examination Report (PCT/IPEA/409). A copy of the International Search Report (PCT/ISA/210). 12. Items 13 to 20 below concern document(s) or information included: An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 13. An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 14.

15. A FIRST preliminary amendment. A SECOND or SUBSEQUENT preliminary amendment. 16

17.

A substitute specification.

☐ A change of power of attorney and/or address letter. 18.

☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. 19.

☐ A second copy of the published international application under 35 U.S.C. 154(d)(4). 20.

A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 21

22. Certificate of Mailing by Express Mail

Other items or information: 23.

> Patent application including 9 pages of specification, 2 pages of claims, 3 sheets or drawings and 1 page of abstract; Check in the amount of \$1000 and \$40 for Fling Fee and Assignment Recordation; Form 1449, PCT/IB/308, Return Postcard

• /						Rec'd P	C.,	21 JL	JN 2001
J.S. AF	PLICATION	NO. (IF KNOWN, SEI	37, CFB 0	INTERNATIONAL AP	PLICATION	ON NO.			OOCKET NUMBER
	, тов	E ASSICAÇÃO	0700	PCT/FI9	9/01063	3	_		3USWO
24.		lowing fees are subr					ŀ	CALCULATIONS	PTO USE ONLY
BASIC	Neither inte	L FEE (37 CFR 1. rnational preliminary I search fee (37 CFR ional Search Report	examination (1.445(a)(2))	fee (37 CFR 1.482) not paid to USPTO by the EPO or JPO	r 	\$1000	.00		
	Internationa USPTO but	l preliminary examin International Search	nation fee (37 Report prepa	CFR 1.482) not paid to red by the EPO or JPO		\$860	.00		
	Internationa but internati	l preliminary examin onal search fee (37 t	nation fee (37 CFR 1.445(a)	CFR 1.482) not paid to (2)) paid to USPTO	USPTO		.00		
	but all clain	ns did not satisfy pro	visions of PC	CFR 1.482) paid to US TArticle 33(1)-(4)		\$690	.00		
	Internationa and all clair	ns satisfied provision	ns of PCT Art	CFR 1.482) paid to US icle 33(1)-(4)		\$100	.00		
				ATE BASIC FEI				\$1,000.00	
Surcha nonth:	rge of \$130. from the ea	00 for furnishing the rliest claimed priorit	oath or decla y date (37 CI	ration later than FR 1.492 (e)).	□ 20			\$0.00	
CL	AIMS	NUMBER	FILED	NUMBER EXTE	LA.	RATE	_	40.00	
Total c	laims	9	- 20 =	0		x \$18.00		\$0.00	
	ndent claims		- 3 =	0		x \$80.00	<u>'</u>	\$0.00 \$0.00	
Multip	le Depender	t Claims (check if a		ABOVE CALC	III AT		=	\$1,000.00	
A A	pplicant cla	ims small entity statu		R 1.27). The fees indic				\$0.00	
in					SUB	TOTAL	= 1	\$1,000.00	
Drobac	sing fee of \$ s from the ea	130.00 for furnishin arliest claimed priori	g the English ty date (37 C	translation later than FR 1.492 (f)).	□ 20		+	\$0.00	
ech				TOTAL NATI	ONAI	LFEE	=	\$1,000.00	
Fee fo	r recording t panied by ar	he enclosed assignm appropriate cover s	ent (37 CFR 1 heet (37 CFR	3.28, 3.31) (check if a	nt must b	ж е).		\$0.00	
01				TOTAL FEES			=	\$1,000.00	
- No								Amount to be: refunded	\$
C 3								charged	\$
a. b.	☐ Ple	ase charge my Depo	sit Account N		bove fee		l.	to cover t	he above fees.
c.	A duplicate copy of this sheet is enclosed. c. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 50-1038 A duplicate copy of this sheet is enclosed.								
d.									
NOTI	E. Where a	n annronriate time	limit under 3	7 CFR 1.494 or 1.495 re the application to p	has not l	een.met. a		1 1/1 1	
1		RESPONDENCE TO		re the apparent to p			M	/ Will	
	nael B. Lask ra Law Gro					SIGNATI	JRE	No	
	City West					Michael	В. І.	asky	
	neapolis, Mi ed States	nnesota 55343				NAME			
Unit	ed States					29,555			
							RATIO	ON NUMBER	
						21 June			
						DATE	2001		
l						DATE			

Serie.

531 Rec'd PCT.

PCT. 21 JUN 2001

S/N UNKNOWN

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:

Palviainen

Serial No .:

TO BE ASSIGNED

Filed:

21 June 2001

Docket No .:

781.403USWO

Title:

CALL ROUTING

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number: EL477364477US

Date of Deposit: 21 June 2001

I hereby certify that this correspondence is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 on the date indicated above and is addressed

to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Name: Kari Arnold

PRELIMINARY AMENDMENT

Box Patent Application Assistant Commissioner for Patents Washington, D.C. 20231

Dear Sir:

Please enter the following preliminary amendment into the above-referenced application.

ABSTRACT

Please insert the attached abstract into the application as the last page thereof.

SPECIFICATION

Enclosed is a copy of Form PCT/IB/308 for PCT Application Number

PCT/FI99/01063 indicating communication of the international application to the

Designated Offices. A courtesy copy of the present specification is enclosed herewith,
but the World Intellectual Property Office (WIPO) copy should be relied upon if it is
already in the U.S. Patent Office.

CLAIMS

Please amend claims 1-9 as follows. A clean copy of the amended claims is included below. A marked up copy of the entire claim set is included in Appendix A.

 (Amended) A method of routing a terminating call in a mobile communication system comprising exchanges which are connected to each other by communication paths, and at least one subscriber database containing subscriber data, said method comprising:

transmitting a request from a routing exchange to said subscriber database, said request including at least a B-subscriber number of said terminating call, wherein retrieving a basic service code for said terminating call from said subscriber database on the basis of the B-subscriber number included in the request, transmitting a response from said subscriber database to said routing

exchange, said response including at least said basic service code, and routing said terminating call from the routing exchange to said B-subscriber number by using communication paths that fulfill the property requirements of the call

(Amended) A method according to claim 1, wherein said subscriber database is a home location register, and that said response is a SendRoutingInfoResE message wherein the basic service code is included.

type indicated by said basic service code.

3. (Amended) A mobile communication system comprising: at least one subscriber database containing subscriber data, and exchanges connected to each other by communication paths, at least one of said exchanges comprising means for transmitting a request to said subscriber database, said request including at least a B-subscriber number of a terminating call, wherein

said subscriber database comprises means for retrieving and transmitting to said exchange a basic service code that corresponds to the B-subscriber number included in the request, and

said exchange comprises means for routing said terminating call to the Bsubscriber number by using communication paths that fulfill the property requirements of the call type indicated by said basic service code.

- 4. (Amended) A mobile communication system according to claim 3, wherein said subscriber database is a home location register, and that said response is a SendRoutingInfoResE message wherein the basic service code is included.
- 5. (Amended) A mobile communication system according to claim 3, wherein said exchange comprises means for subjecting the B-subscriber number to a predetermined conversion selected according to the call type indicated by the basic service code.
- 6. (Amended) A mobile communication system according to claim 3, wherein said exchange comprises means for converting the transmission medium requirement of the terminating call according to the call type indicated by the basic service code.
- (Amended) An exchange of a mobile communication system, said exchange comprising:

means for transmitting a request that includes at least a B-subscriber number of a terminating call, and

routing means for routing said terminating call, wherein

that said exchange comprises means for receiving a basic service code, and that said routing means are responsive to the received basic service code for routing said terminating call to the B-subscriber number by using a communication path that fulfills the property requirements of the call type indicated by said basic service code.

- An exchange according to claim 7, wherein said exchange comprises means for subjecting the B-subscriber number to a predetermined conversion selected according to the call type indicated by the basic service code.
- 9. (Amended) An exchange according to claim 7, wherein said exchange comprises means for converting the transmission medium requirement of the terminating call according to the call type indicated by the basic service code.

REMARKS

The above preliminary amendment is made to insert an abstract page into the application and to amend claims 1-9.

Applicant respectfully requests that this preliminary amendment be entered into the record prior to calculation of the filing fee and prior to examination and consideration of the above-identified application.

If a telephone conference would be helpful in resolving any issues concerning this communication, please contact Applicant's attorney of record, Michael B. Lasky at 952-912-0527.

Respectfully submitted,

Altera Law Group, LLC 6500 City West Parkway, Suite 100 Minneapolis, MN \$5344

Phone No. 952/9/12-0527

Date: 21 June 2001 By:

Michael B. Lasky Reg. No. 29,555

MBL/ssh

E AND AND CARE

ļ.

09/869001 531 Rec'd PC 21 JUN 2001

Appendix A Marked Up Version of the Amended Claims

1. (Amended) A method of routing a terminating call in a mobile communication system comprising exchanges which are connected to each other by communication paths, and at least one subscriber database containing subscriber data, said method comprising:

transmitting a request from a routing exchange to said subscriber database, said request including at least a B-subscriber number of said terminating call, [c h a r a c t e r i z e d by] wherein

retrieving a basic service code for said terminating call from said subscriber database on the basis of the B-subscriber number included in the request.

transmitting a response from said subscriber database to said routing exchange, said response including at least said basic service code, and

routing said terminating call from the routing exchange to said B-subscriber number by using communication paths that fulfill the property requirements of the call type indicated by said basic service code.

- 2. (Amended) A method according to claim 1, [c h a r a c t e r i z e d in that] wherein said subscriber database is a home location register, and that said response is a SendRoutingInfoResE message wherein the basic service code is included.
- 3. (Amended) A mobile communication system comprising: at least one subscriber database [(HLR)] containing subscriber data, and exchanges [(GMSC, MSC)] connected to each other by communication paths [(L1, L2)], at least one of said exchanges [(GMSC)] comprising means for transmitting a

request [(2.2)] to said subscriber database [(HLR)], said request including at least a Bsubscriber number of a terminating call, [c h a r a c t e r i z e d in that] wherein

said subscriber database [(HLR)] comprises means for retrieving and transmitting to said exchange [(GMSC)] a basic service code that corresponds to the B-subscriber number included in the request [(2.2)], and

said exchange [(GMSC)] comprises means [(1)] for routing said terminating call to the B-subscriber number by using communication paths [(L1)] that fulfill the property requirements of the call type indicated by said basic service code.

- 4. (Amended) A mobile communication system according to claim 3, [c h a r a c t e r i z e d in that] wherein said subscriber database [(HLR)] is a home location register, and that said response is a SendRoutingInfoResE message wherein the basic service code is included.
- 5. (Amended) A mobile communication system according to claim 3[or 4], [c h a r a c t e r i z e d in that] wherein said exchange [(GMSC)] comprises means [(2)] for subjecting the B-subscriber number to a predetermined conversion selected according to the call type indicated by the basic service code.
- 6. (Amended) A mobile communication system according to claim 3[or 4], [c h a r a c t e r i z e d in that] wherein said exchange [(GMSC)] comprises means for converting the transmission medium requirement of the terminating call according to the call type indicated by the basic service code.
- (Amended) An exchange [(GMSC)] of a mobile communication system, said exchange comprising:

means for transmitting a request [(2.2)] that includes at least a B-subscriber number of a terminating call, and

routing means [(1)] for routing said terminating call, [characterized in that] wherein

that said exchange [(GMSC)] comprises means for receiving a basic service code, and

that said routing means [(1)] are responsive to the received basic service code for routing said terminating call to the B-subscriber number by using a communication path [(L1)] that fulfills the property requirements of the call type indicated by said basic service code.

- 8. (Amended) An exchange according to claim 7, [c h a r a c t e r i z e d in that] wherein said exchange [(GMSC)] comprises means [(2)] for subjecting the B-subscriber number to a predetermined conversion selected according to the call type indicated by the basic service code.
- 9. (Amended) An exchange according to claim 7, [c h a r a c t e r i z e d in that] wherein said exchange [(GMSC)] comprises means [(2)] for converting the transmission medium requirement of the terminating call according to the call type indicated by the basic service code.

ABSTRACT for CALL ROUTING

The present invention relates to a mobile communication system comprising: at least one subscriber database containing subscriber data, and exchanges connected to each other by communication paths, at least one of said exchanges comprising means for transmitting a request to said subscriber database, said request including at least a B-subscriber number of a terminating call. To provide a system which is capable of selecting the optimum communication path for a terminating call said subscriber database comprises means for retrieving and transmitting to said exchange a basic service code that corresponds to the B-subscriber number included in the request, and said exchange comprises means for routing said terminating call to the B-subscriber number by using communication paths that fulfill the property requirements of the call type indicated by said basic service code.

Call routing

5

The present invention relates to telecommunication systems and especially to a solution for routing a mobile terminating call.

Modern mobile communication systems provide mobile stations with different data transmission properties in addition to conventional speech transmission. Mobile system services can be divided generally into teleservices and bearer services. A bearer service is a telecommunication service that constitutes the transmission of signals between user-network 10 interfaces. For example modern services are bearer services. In a teleservice. the network also provides terminal services. Important teleservices in turn include speech, facsimile and videotex services.

One mobile subscriber may typically have access to different teleand bearer services that are referred to in this connection as basic services. A subscriber may use for example a speech, facsimile and data service. A call terminating at or originating from a mobile station may therefore require any of these basic services, and therefore the correct service must be indicated to the mobile network. For example in a GSM mobile system, call set-up signaling transmitted by a mobile station contains data about the required basic service in a bearer capability information element (BCIE). In this manner, the mobile network is able to select the correct basic service for calls originating from the mobile station. Calls arriving from an Integrated Services Data Network (ISDN) also contain a corresponding information element that indicates the required service. However, if the call arrives from an analog 25 Public Switched Telephone Network (PSTN) or travels through it, the mobile network does not receive such data concerning the service type of the call or the applicable Transmission Medium Requirement (TMR). In such a case, the mobile network should know in some other manner the type of the call in order to be able to route it on appropriate transmission paths.

A known solution to provide information about the call type is to 30 use a multi numbering scheme, where a mobile subscriber has as many directory numbers as he has services to which he wants to receive incoming calls. The number is also called the mobile subscriber ISDN number, i.e. MSISDN. For example, a subscriber may have a number for a speech service. 35 a facsimile service and a modern service. In a multi numbering scheme, the calling subscriber, in other words the A-subscriber, selects from the mobile

subscriber's numbers the B-subscriber number corresponding to the desired service. This prior art solution makes it possible to provide information to the Home Location Register (HLR) of the called mobile station, in other words the B-subscriber, about the type of the terminating call. However, it is not sufficient that only the HLR register is informed about the call type but instead this information should be provided for the network elements that route the call to the B-subscribers. The problem with prior art solutions has been that the HLR register has not been able to provide the necessary information about the call type for the other network elements in such a way that also older existing exchanges would be able to utilize this information efficiently.

The object of the invention is to provide a solution which enables routing of a call in a mobile communication system in an optimal manner which takes into account the call type, and which requires as few modifications as possible to the existing network elements. These objects are achieved with a method of routing a terminating call in a mobile communication system comprising exchanges which are connected to each other by communication paths, and at least one subscriber database containing subscriber data, said method comprising: transmitting a request from a routing exchange to said subscriber database, said request including at least a B-subscriber number of said terminating call. The method of the present invention is characterized by retrieving a basic service code for said terminating call from said subscriber database on the basis of the B-subscriber number included in the request, transmitting a response from said subscriber database to said routing exchange, said response including at least said basic service code, and 25 routing said terminating call from the routing exchange to said B-subscriber number by using communication paths that fulfill the property requirements of the call type indicated by said basic service code.

The present invention also relates to a mobile communication system in which the method of the present invention can be used. The mobile communication system of the invention comprises: at least one subscriber database containing subscriber data, and exchanges connected to each other by communication paths, at least one of said exchanges comprising means for transmitting a request to said subscriber database, said request including at least a B-subscriber number of a terminating call. The mobile communication system is characterized in that said subscriber database comprises means for retrieving and transmitting to said exchange a basic service code that

5

corresponds to the B-subscriber number included in the request, and said exchange comprises means for routing said terminating call to the Bsubscriber number by using communication paths that fulfill the property requirements of the call type indicated by said basic service code.

The invention also relates to an exchange of a mobile communication system which can be used in the mobile communication system of the present invention. The exchange according to the invention comprises: means for transmitting a request that includes at least a Bsubscriber number of a terminating call, and routing means for routing said 10 terminating call. The exchange of the present invention is characterized in that said exchange comprises means for receiving a basic service code, and that said routing means are responsive to the received basic service code for routing said terminating call to the B-subscriber number by using a communication path that fulfills the property requirements of the call type 15 indicated by said basic service code.

The present invention is based on the idea that the exchange which is routing the call is provided with the basic service code of the terminating call. The basic service code indicates the type of the call, and thus the routing exchange is able to determine the properties, for instance quality or 20 transmission speed, that are required by the terminating call. This makes it possible to select the communication paths with the appropriate properties when the call is routed to the B-subscriber number.

The most significant advantages of the present invention are thus that a terminating call from an analog network can be routed in an optimal 25 manner in view of the call type, even though the analog network does not provide any information about the call type. The present invention makes it possible to provide the routing exchange with the basic service code that indicates the call type without any significant changes to existing standards, as this information can be transmitted from the subscriber database to the 30 exchange for instance in a SendRoutingInfoResE message which in existing systems already is transmitted from the Home Location Register (HLR) to the routing exchange.

In a preferred embodiment of the exchange of the present invention, the exchange is provided with means for converting the 35 Transmission Medium Requirement (TMR) of the terminating call according the call type indicated by the basic service code. Analog networks are not

capable of indicating the correct TMR to the exchange of modern digital mobile communication systems. However, the exchanges of present mobile communication systems are capable of indicating the correct TMR to each other when the call is routed. Thus it is sufficient if the first exchange, in other 5 words the Gateway Mobile Switching Centre, can make the necessary TMR conversion for the terminating call. The converted TMR is then forwarded to the other exchanges which participate in the call establishment in a manner known per se. Thus, the other exchanges are capable of routing the call to the appropriate communication paths based on the TMR. Thus the invention can 10 be used with already existing exchanges, and it is sufficient to only make changes to the first exchange GMSC.

In another preferred embodiment of the exchange of the present invention the exchange is provided with means for subjecting the B-subscriber number to a predetermined conversion selected according to the call type indicated by the basic service code. In this preferred embodiment the first exchange GMSC modifies the B-subscriber number for instance by adding a specific predetermined prefix to the number. This prefix is selected such that the other exchanges which participate in the call establishment of the terminating call are able to select suitable communication paths for the call 20 type based on the prefix.

The preferred embodiments of the method, mobile communication system and exchange of the present invention are disclosed in the accompanying dependent claims 2, 4 - 6 and 8 - 9.

The invention will be described in greater detail in connection with 25 preferred embodiments and with reference to the accompanying drawings, in which

Figure 1 is a block diagram illustrating the basic components of a GSM system.

Figure 2 illustrates the set-up of a call terminating at a mobile 30 station (MS) in a GSM-type mobile system,

Figure 3 illustrates the general implementation of subscriber data in a home location register (HLR),

Figure 4 shows an example of a response from an HLR to an exchange, and

35 Figure 5 is a flow chart of a first preferred embodiment of the method of the present invention.

The present invention is applicable for use in mobile systems where circuit switched data and speech calls can be set up. The invention can be used especially in a GSM mobile system and in similar more recent mobile systems, such as the GSM 900, GSM1800 and the GSM 1900. In the 5 following, the primary embodiment of the invention will be described in the GSM system, without restricting the invention thereto, however.

Figure 1 shows the basic components of the GSM system without describing in greater detail their properties or other parts of the system. For a more detailed description of the GSM system, reference is made to the GSM 10 recommendations and The GSM System for Mobile Communications by M. Mouly and M. Pautet, Palaiseau, France, 1992, ISBN:2-9507190-0-0-7

A mobile services switching centre MSC manages the switching of incoming and outgoing calls. It carries out similar functions as an exchange in a PSTN. In addition, it also performs functions, such as subscriber location management, that are only characteristic of mobile communication in connection with the network subscriber registers. In a GSM system, the subscriber registers include a home location register HLR and a visitor location register VLR. Subscriber data is stored permanently in the home location register HLR, as well as information on the visitor location register VLR in the area of which the MS is located. The visitor location register VLR in turn stores subscriber data of an MS temporarily while the MS is located in the area of the mobile services switching centre MSC connected to the visitor location register VLR. One visitor location register VLR typically serves one mobile services switching centre MSC. The MSs are connected to the mobile services 25 switching centre MSC via base station systems BSS. A base station system BSS is formed of base station controllers BSC and base stations BTS. One base station controller BSC is used to control several base stations BTS.

Figure 2 illustrates the formation of a call terminating at a mobile station MS according to the present invention in a GSM-type mobile system 30 utilizing a multi numbering scheme. In step 2.1, a call arrives at a first exchange GMSC of the network, which transmits a routing information request (message 2.2) to the subscriber home location register HLR that is determined according to the subscriber number MSISDN. The routing information request message 2.2 also contains the MSISDN, in other words the B-subscriber 35 number. In location updating, the home location register HLR of the subscriber is provided with updated data about the visitor location register VLR in the

area of which the subscriber is located. On the basis of this data, the home location register HLR transmits a roaming number allocation request (message 2.3) to the visitor location register VLR. With the roaming number allocation request the visitor location register VLR also receives an international mobile 5 subscriber identity (IMSI) and the BCIE related to the called MSISDN (or the ISDN BCIE that arrived in the message 2.2), indicating for example the network resources required by the call but not the type of the basic service. The visitor location register VLR stores the BCIE it has received and allocates a mobile station roaming number (MSRN) (event 2.4). The visitor location 10 register VLR transmits the allocated MSRN to the home location register HLR in a response message 2.5.

The Home Location Register comprises a register from which it is able to retrieve the basic service code corresponding to the B-subscriber number included in the request 2.2. The home location register is thus able to transmit a message 2.6 with the roaming number and the basic service code to the exchange GMSC that requested for the routing information. The roaming number space is determined such that a call is always directed to the visited MSC the visitor location register VLR of which has allocated the roaming number.

A routing means 1 of the exchange GMSC uses the information in the response 2.6 for routing the terminating call. In the example of Figure 2 the routing exchange GMSC is connected by two communication paths or lines L1 and L2 to the exchange MSC. Lines L1 and L2 are assumed to have different properties such that, for instance, line L1 is suitable for data calls and line L2 25 for ordinary speech calls. The exchange GMSC is able to determine the type of the terminating call which is indicated by the basic service code included in the response 2.6. Thus, if the basic service code indicates that the terminating call is a data call, then the GMSC selects line L1 when it routes the call to the exchange MSC. Correspondingly, if the basic service code indicates that the 30 terminating call is a data call, then the GMSC selects line L1 when it routes the call to the exchange MSC.

The exchange GMSC also comprises conversion means 2, which convert the information relating to the terminating call such that subsequent exchanges of the mobile communication system are able to route the call over 35 the appropriate lines. This can be achieved such that the conversion means convert the Transmission Medium Requirement (TMR) of the terminating call

J

30

10

when ISDN signaling (ISUP) is in use. Existing prior art exchanges in mobile communication systems which utilize ISDN signaling are capable of selecting appropriate communication paths based on the TMR. However, an analog PSTN network is not able to provide the GMSC with the correct TMR. Thus, 5 according to the present invention, the exchange GMSC communicates with the HLR register in order to obtain the basic service code of the terminating call, and on the basis of this information it converts the TMR of the terminating call such that the other exchanges of the network are able to use it and to select an appropriate line for the call.

Another alternative for providing information about the call type to the subsequent exchanges is that the conversion means 2 convert the Bsubscriber number in a predetermined manner, for instance by adding a prefix to the B-subscriber number. This prefix is selected such that it informs the subsequent exchanges about the call type.

When the exchange GMSC has received the response 2.6, identified the call type and carried out the necessary conversions it transmits an initial message 2.7 to the exchange MSC indicated by the roaming number. This initial message is transmitted on line L1 or line L2 depending on the call type.

After the exchange MSC has received the initial address message 2.7, it finds during the roaming number analysis that the call is about to terminate in its own area and should not be forwarded. In such a case, the exchange MSC asks for the data of the called subscriber from its own visitor location register VLR for the purpose of call set-up (message 2.8). In a normal 25 situation, the visitor location register VLR returns the required data, including for example the BCIE, in a response message 2.9. If the exchange MSC is capable of providing the data transmission resources indicated by the BCIE, the call set-up signaling illustrated by arrows 2.10 and 2.11 will be carried out between the exchange MSC and the mobile station MS.

As described above, modern mobile systems support different teleand bearer services. The GSM bearer services are determined in GSM recommendation 02.02 and the teleservices in GSM recommendation 02.03. A separate teleservice and bearer service code is determined for each teleservice and bearer service in recommendation 09.02. For example, the 35 teleservice code of the speech service is 00010001 and the teleservice code of the short messages originating from a mobile station is 00100010. In this

specification, all service codes are called basic service codes. One mobile subscriber may have access to different tele- and bearer services, which are referred to in this connection as basic services. As described above, it is preferable to use a multi numbering scheme, where each basic service is allocated an individual MSISDN.

In a GSM system, subscriber services are specified in a subscriber home location register HLR with the other subscriber data. Figure 3 illustrates the general implementation of subscriber data in the home location register HLR for a subscriber that has access to n basic services. The subscriber has his own IMSI that is used as subscriber identification within the mobile network. The services specified for the subscriber are related to the subscriber IMSI. According to the principle of the multi numbering scheme, each subscriber service 1 to n is given an individual number MSISDN-1 to MSISDN-n. Each MSISDN is related to one basic service code SC-1 to SC-n that determines the service. The basic service code is one of the aforementioned tele- and bearer service codes.

Figure 4 shows an example of a response (SendRoutingInfoResE, SRI-Res) from an HLR to a request for routing information. In the embodiment described herein, the response message returns the basic service code SC-n ([9]basicService) related to the called party number (B-subscriber number) and stored in the HLR to the exchange that made the routing request. According to the invention, the exchange GMSC identifies the type of the service on the basis of the basic service code and selects a line, in other words a communication path, for routing the call to the B-subscriber number according to the type of call indicated by the basic service code. The communication path is selected such that the exchange selects from several optional lines with different properties, a line that fulfills the property requirements of the call type in question.

Figure 5 is a flow chart of a first preferred embodiment of the 30 present invention. The flow chart of Figure 5 can be used for instance in a GSM system where a multi numbering scheme is used.

In block A a first exchange GMSC of a mobile communication system receives information for a call terminating at a mobile subscriber. The call originateds from an analog PSTN network, and thus the GMSC does not receive information which would make it possible to identify the call type. The

20

GMSC transmits a routing request with the B-subscriber number to the Home Location Register HLR of the mobile station in question.

In block B the HLR register retrieves the basic service code corresponding to the B-subscriber number. The HLR also transmits a roaming 5 number request to a VLR register and receives a Mobile Station Roaming Number (MSRN) (as described in more detail in connection with Figure 2).

block C the HLR register transmits а (SendRoutingInfoResE, SRI-Res) to the GMSC. Said response includes the retrieved basic service code of the terminating call.

In block D the GMSC converts the information relating to the terminating call such that subsequent exchanges, which also participate in the routing of the terminating call, are able to route the call on communication paths with appropriate properties for the call type in question. In a system where ISDN signaling (ISUP) is in use, this can be achieved for instance such 15 that the Transmission Medium Requirement (TMR) of the terminating call is converted according to the call type indicated by the basic service code.

In block E the GMSC routes the call to the B-subscriber number by using a communication path with appropriate properties for the call type in question.

It should be understood that the above description and the related drawings are only intended to illustrate the present invention. Thus variations and modifications from the description will be apparent to those skilled in the art without departing from the scope and spirit of the invention disclosed in the attached claims.

30

Claims

1. A method of routing a terminating call in a mobile communication system comprising exchanges which are connected to each other by communication paths, and at least one subscriber database containing subscriber data, said method comprising:

transmitting a request from a routing exchange to said subscriber database, said request including at least a B-subscriber number of said terminating call, characterized by

retrieving a basic service code for said terminating call from said subscriber database on the basis of the B-subscriber number included in the request.

transmitting a response from said subscriber database to said routing exchange, said response including at least said basic service code, 15 and

routing said terminating call from the routing exchange to said Bsubscriber number by using communication paths that fulfill the property requirements of the call type indicated by said basic service code.

- 2. A method according to claim 1, characterized in that said subscriber database is a home location register, and that said response is a SendRoutingInfoResE message wherein the basic service code is included.
 - A mobile communication system comprising:

at least one subscriber database (HLR) containing subscriber data, and

exchanges (GMSC, MSC) connected to each other by communication paths (L1, L2), at least one of said exchanges (GMSC) comprising means for transmitting a request (2.2) to said subscriber database (HLR), said request including at least a B-subscriber number of a terminating call, characterized in that

said subscriber database (HLR) comprises means for retrieving and transmitting to said exchange (GMSC) a basic service code that corresponds to the B-subscriber number included in the request (2.2), and

said exchange (GMSC) comprises means (1) for routing said terminating call to the B-subscriber number by using communication paths (L1) that fulfill the property requirements of the call type indicated by said basic service code.

15

25

- 4. A mobile communication system according to claim 3, characterized in that said subscriber database (HLR) is a home location register, and that said response is a SendRoutingInfoResE message wherein the basic service code is included.
- 5. A mobile communication system according to claim 3 or 4, characterized in that said exchange (GMSC) comprises means (2) for subjecting the B-subscriber number to a predetermined conversion selected according to the call type indicated by the basic service code.
- 6. A mobile communication system according to claim 3 or 4, 10 characterized in that said exchange (GMSC) comprises means for converting the transmission medium requirement of the terminating call according to the call type indicated by the basic service code.
 - 7. An exchange (GMSC) of a mobile communication system, said exchange comprising:

means for transmitting a request (2.2) that includes at least a B-subscriber number of a terminating call, and

routing means (1) for routing said terminating call, characterized in

that said exchange (GMSC) comprises means for receiving a basic 20 service code, and

that said routing means (1) are responsive to the received basic service code for routing said terminating call to the B-subscriber number by using a communication path (L1) that fulfills the property requirements of the call type indicated by said basic service code.

- 8. An exchange according to claim 7, characterized in that said exchange (GMSC) comprises means (2) for subjecting the B-subscriber number to a predetermined conversion selected according to the call type indicated by the basic service code.
- 9. An exchange according to claim 7, characterized in that 30 said exchange (GMSC) comprises means (2) for converting the transmission medium requirement of the terminating call according to the call type indicated by the basic service code.





FIG. 1



IMSI	MSISDN-1	SC-1	MSISDN-2	SC-2	 MSISDN-n	SC-n
111101	2.202					

FIG. 3

SendRoutingInfoResE ::= SEQUENCE (imsi IMSI, routingInfo RoutingInfo, cug-CheckInfo CUG-Checkinfo OPTIONAL. PnpIndex OPTIONAL, pni OPTIONAL, sriResExtension [PRIVATE 0] SriResExtension [PRIVATE 30] ANSISriResExt ansiSriResExt OPTIONAL

SriResExtension inTriggerKey virNumber activeSs traceReference traceType omc-Id hotBilling cfolsDone cfinCug basicService category routingCategory pnplndex nokia-CUG noBarrings odb-Data	::= [PRIVATE 0] [0] [1] [2] [3] [4] [5] [6] [7] [8] [9] [10] [11] [12] [13] [14] [15]	SEQUENCE (InTriggerKey ISDN-AddressString ActiveSS-List TraceReference TraceType AddressString BOOLEAN BOOLEAN BOOLEAN BOOLEAN BasicServiceCode Category RoutingCategory PnpIndex Nokia-CUG-Data NULL ODB-Data	OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL, OPTIONAL,
)	•		

THE GMSC TRANSMITS A REQUEST WITH A B-SUBSCRIBER NUMBER TO THE HLR THE HLR RETRIEVES THE BASIC SERVICE CODE CORRESPONDING TO THE RECEIVED В **B-SUBSCRIBER NUMBER** THE HLR TRANSMITS A RESPONSE WITH THE BASIC SERVICE CODE TO THE GMSC THE GMSC CONVERTS INFORMATION D RELATING TO THE TERMINATING CALL ACCORDING TO THE CALL TYPE INDICATED: BY THE RECEIVED BASIC SERVICE CODE THE GMSC ROUTES THE CALL TO THE E. B-SUBSCRIBER NUMBER BY USING A COMMUNICATION PATH WHICH IS SELECTED ON THE BASIS OF THE RECEIVED BASIC SERVICE CODE

FIG. 5

Altera Law Group, LLC

Declaration and Power of Attorney Patent Application (Design or Utility)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Call routing	
he specification of which	
,	
is referred to by Altera reference number on a separate document is attached hereto	
was filed on <u>21 December 1999</u> as application serial no. and or PCT International Application number PCT/FI99/01063	
and was amended on (if applicable).	

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information know to me to be material to patentability as defined in 37 C.F.R.§1.56.

I hereby claim foreign priority benefits under 35 U.S.C.§119(a)-(d) or 35 U.S.C.§365(b) of any foreign application(s) for patent or inventor's certificate, or 35 U.S.C.§365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate of PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)				
Number	Country	Day/Month/Year Filed		
982762	Finland	21/12/1998		
Number	Country	Day/Month/Year Filed		
Number	Country	Day/Month/Year Filed		

C

Power of Attorney

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

 Steven R. Funk
 Reg. No. 37.839
 David W. Lynch
 Reg. No. 36,204

 Michael B. Lasky
 Reg. No. 29.555
 Karen D. McDaniel
 Reg. No. 37,674

 Jain A. Molntvre
 Reg. No. 40.337
 Reg. No. 40.337

I hereby authorize them or others whom they may appoint to act and rely on instructions from and communicate directly with the person/organization who/which first sends this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct Altera Law Group, LLC otherwise.

Please direct all correspondence in this case to Altera Law Group, LLC at the address indicated below:

Altera Law Group, LLC 10749 Bren Road East, Opus 2 Minneapolis, MN 55343

	Full Name of Sole or First Inventor	
Family Name	First Given Name	Second Given Name
Palviainen	Keijo	Lauri
	Residence and Citizenship	
City of Residence	State or Country of Residence	Country of Citizenship
Helsinki	Finland FTV	Finland
	Post Office Address	
Street Address	City	State & Zip Code or Country
Halmetie 6 A 2	Helsinki	00700, Finland
Signature of Inventor		Date
Bo, lem		June 1 st , 2001

	Full Name of Second Inventor, if	any
Family Name	First Given Name	Second Given Name
	Residence and Citizenship	
City of Residence	State or Country of Residence	Country of Citizenship
	Post Office Address	
Street Address	City	State & Zip Code or Country
Signature of Inventor		Date

100



I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below:

Day/Month/Year Filing Date	
Day/Month/Year Filing Date	
Day/Month/Year Filing Date	
	Day/Month/Year Filing Date

I hereby claim the benefit under 35 U.S.C. \$120 of any United States application(s), or under 35 U.S.C. \$365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R.§1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

Prior U.S. or International Application(s)				
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)		
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)		
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)		

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C.§1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.